PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION



101	Interna	ational Bureau
INTERNATIONAL APPLICATION PUBLISH	IED U	JNDER THE PATENT COOPERATION TREATY (PCT)
(51) International Patent Classification 7:		(11) International Publication Number: WO 00/04104
C09D 11/00	A1	(43) International Publication Date: 27 January 2000 (27.01.00)
(21) International Application Number: PCT/US9 (22) International Filing Date: 20 July 1999 (2 (30) Priority Data: 60/093,458 20 July 1998 (20.07.98)	20.07.9	BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI,
(71) Applicant: KIMBERLY-CLARK WORLDWIDE [US/US]; 401 North Lake Street, Neenah, WI 5495	E, IN 56 (US	C. FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(72) Inventors: NOHR, Ronald, Sinclair, 8955 Nesbit Lake Alpharetta, GA 30202 (US). MCDONALD, John 1472 Knollwood Terrace, Decatur, GA 30033 (US) (74) Agents: WITHERS, James, D.; Jones & Askew, LI	i, Gav i).	Published With international search report.
Monarch Tower, 3424 Peachtree Road, Atlanta, G (US) et al.	iA 303	26

(54) Title: IMPROVED INK JET INK COMPOSITIONS

(57) Abstract

The present invention is directed to compositions containing a colorant and at least one water-soluble solvent, wherein the water-soluble solvent is a compound having general formula (I): wherein x is hydrogen or an alkyl having from 1 to 6 carbons; y is an alkyl having from 1 to 6 carbons; and z is an alkyl having from 1 to 6 carbons.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	. LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		•
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

10

IMPROVED INK JET INK COMPOSITIONS

Technical Field

The present invention relates to colorant compositions, particularly to ink jet ink compositions.

15

20

25

Background of the Invention

The use of pyrrolidone and glycols as suitable "solvents" in colorant compositions is well known in the art of ink jet printing. For example, U.S. Patent No. 5,108,503 to Hindagolla et al., assigned to Hewlett-Packard Company, Palo Alto, CA, disclosed ink jet ink compositions containing one or more solvents in the form of pyrrolidones. Other ink compositions containing glycols as suitable solvents are disclosed in numerous patents including, but not limited to, U.S. Patents Nos. 3,705,043; 4,381,946; 4,421,559; 4,853,037; 4,957,533; 4,973,499; 5,196,057; 5,207,824; 5,431,724; 5,560,771; and 5,624,484.

30

The above-mentioned ink compositions, containing one or more pyrrolidone and/or glycols, result in a hazy or dull color when applied to a number of ink-receiving substrates. Further, the above-described ink compositions possess an undesirable degree of tackiness when applied to a number of ink-receiving substrates. While the above-described ink compositions have a number of desirable properties, such as

10

15

20

minimal spreading, smear resistance and waterfastness, the ink compositions still possess many shortcomings.

What is needed in the art is an ink jet ink composition which may be applied to an ink-receiving substrate without resulting in a hazy appearance or a tacky feel.

Summary of the Invention

The present invention is directed to compositions containing a colorant and at least one water-soluble compound having the following general formula:

$$z - C$$
 $N - y$

wherein x is hydrogen or an alkyl having from approximately 1 to 6 carbons; y is an alkyl having from approximately 1 to 6 carbons. The presence of the water-soluble compound results in an improved composition with minimal haziness and tackiness. In one embodiment of the present invention, the composition comprises an ink jet ink composition. Other compatible components may be added to the mixture to produce a composition having desired properties, such as lightfastness, waterfastness, pH, etc.

The present invention is also directed to ink-receiving substrates having the above-described composition thereon. Suitable ink-receiving substrates include substrates such as paper, wood, fabrics and films. The present invention is further directed to a method of printing an ink composition onto an ink-receiving substrate.

The present invention is also directed to a method of making a composition comprising a colorant and at least one water-soluble compound as described above. At least one

30


WO 00/04104 PCT/US99/16372

water-soluble compound is incorporated into a mixture containing a colorant. The present invention is also directed to an ink jet ink cartridge containing the above-described composition.

These and other features and advantages of the present invention will become apparent after a review of the following detailed description of the disclosed embodiments and the appended claims.

Detailed Description of the Invention

The compositions of the present invention contain a colorant and at least one water-soluble compound having the following general formula:



15

5

10

20

25

30

is hydrogen or an alkyl having from wherein *x* approximately 1 to 6 carbons; y is an alkyl having from approximately 1 to 6 carbons; and z is an alkyl having from approximately 1 to 6 carbons. The compositions possess waterfastness and smear resistance similar to or superior to colorant compositions of the prior art, but also have minimal haziness and tackiness regardless of the ink-receiving The present invention is also directed to inksubstrate. above-described substrates the having receiving composition thereon.

As used herein, the term "composition" and such variations as "colored composition" are used herein to mean a colorant and one or more water-soluble compounds described above. The composition may optionally include other compatible components.

As used herein, the term "colorant" is meant to include, without limitation, any material which typically will be an organic material, such as an organic colorant or dye. The term is meant to include a single material or a mixture of two or more materials.

The term "thereon" is used herein to mean thereon or therein. For example, the present invention includes a substrate having a colored composition thereon. According to the definition of "thereon" the colored composition may be present on the substrate or it may be in the substrate.

The water-soluble compounds used in the compositions of the present invention have the following general formula:

$$z - C$$
 $N - y$

15

20

5

10

wherein x is hydrogen or an alkyl having from 1 to 6 carbons; y is an alkyl having from 1 to 6 carbons. The substituents x, y and z are selected to result in a compound which is water soluble. In some desired embodiments, x is hydrogen; y is an alkyl having from 1 to 3 carbons; and z is an alkyl having from 1 to 3 carbons. In more desired embodiments, x is hydrogen; y is an alkyl having from 1 to 2 carbons; and z is an alkyl having from 1 to 2 carbons; and z is an alkyl having from 1 to 2 carbons.

25

In one embodiment of the present invention, the water-soluble compound comprises

In a further embodiment, the water-soluble compound comprises

5

10

The water-soluble compound may be present in the composition in any amount as long as the composition is suitable for use. For example, when the composition is an ink jet ink composition, the amount of water-soluble compound may need to be less than for another type of coating. Desirably, the amount of water-soluble compound in the composition of the present invention is up to about 25 weight percent based on the total weight of the composition. In some desired embodiments of the present invention, the water-soluble compound is present in an amount of about 2 to 25 weight percent based on the total weight of the composition. In more desired embodiments of the present invention, the water-soluble compound is present in an amount of about 6 to 10 weight percent based on the total weight of the composition.

20

15

The compositions of the present invention may include any colorant known in the art. Suitable colorants include, bur are not limited to, dyes and pigments. Desirably, the colorant is an organic dye. Organic dye classes include, by way of illustration only, triarylmethyl dyes, such as Malachite Green Carbinol base {4-(dimethylamino)-a-[4-(dimethylamino)phenyl]-a-phenyl-benzene-methanol}, Malachite Green Carbinol hydrochloride {N-4-[[4-(dimethylamino)phenyl]phenyl-methylene]-2,5-cyclohexyldien-1-ylidene]-N-methyl-methanaminium chloride or bis[p-(dimethylamino)phenyl]phenylmethylium chloride},

30

10

15

20

25

30

35

and Malachite Green oxalate {N-4-[[4-(dimethylamino)phenyl]-phenylmethylene]-2,5-cyclohexyldien-1-ylidene]-Nmethyl-methanaminium chloride or bis[p-(dimethylamino)phenylphenylmethylium oxalate); monoazo dyes, such as Cyanine Black, Chrysoidine [Basic Orange 2; 4-(phenylazo)-1,3-benzenediamine monohydrochloride], Victoria Pure Blue BO, Victoria Pure Blue B, basic fuschin and ß-Naphthol Orange; thiazine dyes, such as Methylene Green, zinc [3,7-bis(dimethylamino)-6chloride double salt nitrophenothiazin-5-ium chloride, zinc chloride double salt]; oxazine dyes, such as Lumichrome (7,8-dimethylalloxazine); naphthalimide dyes, such as Lucifer Yellow CH {6-amino-2-[(hydrazino-carbonyl)amino]-2,3-dihydro-1,3-dioxo-1Hbenz[de]iso-quinoline-5,8-disulfonic acid dilithium salt}; azine such as Janus Green B {3-(diethylamino)-7-[[4-(dimethyl-amino)phenyl]azo]-5-phenylphenazinium chloride); cyanine dyes, such as Indocyanine Green {Cardio-Green or Fox Green; 2-[7-[1,3-dihydro-1,1-dimethyl-3-(4sulfobutyl)-2H-benz[e]indol-2-ylidene]-1,3,5-heptatrienyl]-1,1-dimethyl-3-(4-sulfobutyl)-1H-benz[e]indolium hydroxide inner salt sodium salt); indigo dyes, such as Indigo (Indigo Blue or Vat Blue 1; 2-(1,3-dihydro-3-oxo-2H-indol-2ylidene)-1,2-dihydro-3H-indol-3-one); coumarin dyes, such 7-hydroxy-4-methyl-coumarin (4-methylumbelliferone); benzimidazole dyes, such as Hoechst 33258 [bisbenzimide or 2-(4-hydroxyphenyl)-5-(4-methyl-1-piperazinyl)-2,5-bi-1Htrihydro-chloride pentahydrate]; benzimidazole paraquinoidal dyes, such as Hematoxylin (Natural Black 1; 7,11b-dihydrobenz[b]-indeno[1,2-d]pyran-3,4,6a,9,10(6H)pentol); fluorescein dyes, such as Fluoresceinamine (5aminofluorescein); diazonium salt dyes, such as Diazo Red RC (Azoic Diazo No. 10 or Fast Red RC salt; 2-methoxy-5chlorobenzenediazonium chloride, zinc chloride double salt); azoic diazo dyes, such as Fast Blue BB salt (Azoic Diazo No. 4-benzoylamino-2,5-diethoxy-benzene diazonium 20;

WO 00/04104 PCT/US99/16372

5

10

15

20

25

30

35

chloride, zinc chloride double salt); phenylenediamine dyes, such as Disperse Yellow 9 [N-(2,4-dinitrophenyl)-1,4phenylenediamine or Solvent Orange 53]; diazo dyes, such as Disperse Orange 13 [Solvent Orange 52; 1-phenylazo-4-(4-hydroxyphenylazo)naphthalene]; anthra-quinone dyes, such as Disperse Blue 3 [Celliton Fast Blue FFR; 1methylamino-4-(2-hydroxyethylamino)-9,10-anthraquinone], Disperse Blue 14 [Celliton Fast Blue B; 1,4-bis(methylamino)-9,10-anthraquinone], and Alizarin Blue Black B (Mordant Black 13); trisazo dyes, such as Direct Blue 71 {Benzo Light Blue FFL or Sirius Light Blue BRR; 3-[(4-[(6-amino-1hydroxy-3-sulfo-2-naphthalenyl)azo]-6-sulfo-1naphthalenyl)-azo]-1-naphthalenyl)azo]-1,5naphthalenedisulfonic acid tetrasodium salt); xanthene dyes, such as 2,7-dichloro-fluorescein; proflavine dyes, such as hemisulfate (Proflavine); 3.6-diaminoacridine Red such Cresol sulfonaphthalein dyes, as phthalocyanine dyes, such cresolsulfonaphthalein); {Pigment Blue (SP-4-1)-15; Phthalocyanine $[29H,31H-phthalocyanato(2-)-N^{29},N^{30},N^{31},N^{32}]copper\};$ carotenoid dyes, such as trans-ß-carotene (Food Orange 5); carminic acid dyes, such as Carmine, the aluminum or carminic acid lake of calcium-aluminum glucopyranosyl-9,10-dihydro-3,5,6,8-tetrahydroxy-1-methyl-9,10-dioxo-2-anthracene-carbonylic acid); azure dyes, such as Azure A [3-amino-7-(dimethylamino)phenothiazin-5-ium 7-(dimethyl-amino)-3-imino-3H-phenothiazine hydrochloride]; and acridine dyes, such as Acridine Orange 3,8-bis(dimethylamino)acridine 14; Basic Orange hydrochloride, zinc chloride double salt] and Acriflavine 3,6-diamino-10-methylacridinium (Acriflavine neutral: chloride mixture with 3,6-acridine-diamine).

The colorant compositions of the present invention may contain a number of additional components depending on the desired properties of the resulting composition. To WO 00/04104 PCT/US99/16372

improve lightfastness, one or more colorant stabilizers may be added to the composition. In one embodiment of the present invention, a colorant stabilizer in the form of a porphine is added to the colorant composition. Suitable porphines include, but are not limited to, porphines such as those disclosed in U.S. Patent No. 5,782,963 and U.S. Patent Applications Serial Nos. 08/788,863 and 08/843,410, all of which are assigned to Kimberly Clark Worldwide, Inc.

5

10

15

20

25

30

35

In addition to the colorant and optional colorant stabilizer, the colored compositions of the present invention may contain additional components, depending upon the application for which it is intended. Examples of such additional components include, but are not limited to, buffering agents; charge carriers; stabilizers against thermal oxidation; viscoelastic properties modifiers; cross-linking agents; plasticizers; charge control additives such as a quaternary ammonium salt; flow control additives such as hydrophobic silica, zinc stearate, calcium stearate, lithium stearate, polyvinylstearate, and polyethylene powders; fillers such as calcium carbonate, clay and talc; surfactants; chelating agents; and TINUVIN® compounds; among other additives used by those having ordinary skill in the art. Charge carriers are well known to those having ordinary skill in the art and typically are polymer-coated metal particles. Desirable surfactants include, but are not limited to, C12 to C18 surfactants such as cetyl trimethyl ammonium car boxymethylamylose.TINUVIN® chloride and compounds are a class of compounds produced by Ciba-Corporation, which includes benzophenones, benzotriazoles and hindered amines. Desirable TINUVIN® compounds include, but are not limited to, 2-(2'-hydroxy-3'poly-(N-ßsec-butyl-5'-tert-butylphenyl)-benzo-triazole, hydroxyethyl-2,2,6,6-tetramethyl-4-hydroxy-piperidyl 2-(2'-hydroxy-3',5'-ditertbutylphenyl)-5chloro-benzotriazole. The identities and amounts of such PCT/US99/16372

WO 00/04104

5

10

15

20

25

30

additional components in the colored composition are well known to one of ordinary skill in the art.

Suitable solvents include, but are not limited to, amides, such as N,N-dimethylformamide; sulfoxides, such as dimethylsulfoxide; ketones, such as acetone, methyl ethyl ketone, and methyl butyl ketone; aliphatic and aromatic hydrocarbons, such as hexane, octane, benzene, toluene, and the xylenes; esters, such as ethyl acetate; water; and the like. Desirably, the solvent is water.

The present invention is also directed to ink-receiving substrates having the above-described composition thereon. The substrates to which the colorant and water-soluble compounds are applied include, but are not limited to, paper, wood, a wood product or composite, woven fabric, nonwoven fabric, textile, plastic, glass, metal, or any other substrate that would benefit from having a colorant thereon. Examples of suitable substrates are disclosed in U.S. Patent Application Serial No. 08/843,410, assigned to Kimberly Clark Worldwide, Inc., the entire content of which is hereby incorporated by reference.

The present invention is also directed to a method of making a composition comprising a colorant and at least one water-soluble compound as described above. At least one water-soluble compound is incorporated into a mixture containing a colorant. The method of combining the colorant and water-soluble compound may be any method known to those of ordinary skill in the art.

The present invention is also directed to an ink jet ink cartridge containing the above-described composition.

The present invention is further directed to a method of printing an ink composition onto an ink-receiving substrate. In one method of printing of the present invention, an ink composition comprising a colorant and at least one water-soluble compound is ejected from an ink jet head onto an ink-receiving surface.

WO 00/04104 PCT/US99/16372

The present invention is further described by the examples which follow. Such examples, however, are not to be construed as limiting in any way either the spirit or the scope of the present invention. In the examples, all parts are by weight, unless stated otherwise.

EXAMPLE 1

Preparation of Magenta Ink

A magenta ink was prepared using the following components, given in weight percent:

DI Water	82.76
NaOH (0.5 N solution)	4.00
CuTPPS ₄	0.50
EDTA	0.10
EuNO ₃	0.05
N-methylpropionamide	8.00
GIV-GUARD® DNX	0.40
(50 wt% solution)	
COBRATEC® 99	0.10
Reactive Red 187	2.89
(27 wt% solution)	
Acid Red 52	1.20

The resulting ink composition was applied to an ink-receiving substrate as described in pending U.S. patent application serial no. 09/058,385, entitled "Improved Substrate and Colorant Stabilizers", assigned to Kimberly Clark Worldwide, Inc. The applied ink composition was free of haze and tackiness.

20

15

5

EXAMPLE 2

Preparation of Magenta Inks

Two additional magenta ink compositions were prepared using the same components as in Example 1 above except the amount of N-methylpropionamide was 6.0 and 10.0 weight percent respectively.

The resulting ink compositions were applied to inkreceiving substrates as in Example 1. The applied ink compositions were free of haze and tackiness.

10

15

5

EXAMPLE 3

Preparation of Cyan Ink

A cyan ink was prepared using the following components, given in weight percent:

DI Water	69.80
NaOH (0.5 N solution)	3.20
N-methylpropionamide	8.00
GIV-GUARD® DNX	0.40
(50 wt% solution)	
COBRATEC® 99	0.10
Project Cyan	18.50

The resulting ink composition was applied to an inkreceiving substrate as in Example 1. The applied ink composition was free of haze and tackiness.

25

20

While the specification has been described in detail with respect to specific embodiments thereof, it will be appreciated that those skilled in the art, upon attaining an understanding of the foregoing, may readily conceive of alterations to, variations of, and equivalents to these

PCT/US99/16372

embodiments. Accordingly, the scope of the present invention should be assessed as that of the appended claims and any equivalents thereto.

10

25

30

Claims

What is claimed is:

1. A composition containing a colorant and at least one water-soluble compound having the following general formula:

$$z - C$$
 $N-y$

wherein x is hydrogen or an alkyl having from 1 to 6 carbons; y is an alkyl having from 1 to 6 carbons; and z is an alkyl having from 1 to 6 carbons.

- 2. The composition of Claim 1, wherein the composition is an ink jet ink composition.
- 3. The composition of Claim 2, wherein the water-soluble compound is present in an amount of up to about 25 weight percent based on the total weight of the composition.
- 20 4. The composition of Claim 3, wherein the water-soluble compound is present in an amount of about 6 to 10 weight percent based on the total weight of the composition.
 - 5. The composition of Claim 3, wherein the composition comprises:
 - (a) from about 2 to about 25 weight percent of the water-soluble compound;
 - (b) from about 1 to about 10 weight percent colorant; and
 - (c) the balance water.

10

15

6. The composition of Claim 1, wherein the water-soluble compound comprises

7. The composition of Claim 1, wherein the water-soluble compound comprises

- 8. The composition of Claim 1, further comprising at least one colorant stabilizer.
- 9. The composition of Claim 8, wherein the colorant stabilizer comprises a porphine.
- 10. A substrate having the composition of Claim 1 thereon.

11. A method of making a composition comprising: combining a colorant and at least one water-soluble compound to form a mixture, wherein the one water-soluble compound has the following general formula:

$$z - C$$
 $N - y$
 x

wherein x is hydrogen or an alkyl having from 1 to 6 carbons; y is an alkyl having from 1 to 6 carbons; and z is an alkyl having from 1 to 6 carbons.

- 12. The method of Claim 11, wherein the composition is an ink jet ink composition.
- 13. The method of Claim 12, wherein the water-soluble compound is present in an amount of up to about 25 weight percent based on the total weight of the composition.
- 14. The method of Claim 13, wherein the water-soluble compound is present in an amount of about 6 to 10 weight percent based on the total weight of the composition.

25

5

10 .

15

15. The method of Claim 11, wherein the water-soluble compound comprises

5

16. The method of Claim 11, wherein the water-soluble compound comprises

$$CH_3CH_2$$
 CH_3
 CH_3
 CH_3
 CH_3

10

17. An ink jet ink cartridge containing the composition of Claim 1.

18. A method of printing an ink composition onto a substrate comprising:

ejecting an ink composition from an ink jet cartridge onto a substrate; wherein the ink composition comprises a colorant and at least one water-soluble compound, wherein the one water-soluble compound has the following general formula:

$$z - \bigcup_{\substack{y \\ x}}^{O}$$

10

5

wherein x is hydrogen or an alkyl having from 1 to 6 carbons; y is an alkyl having from 1 to 6 carbons; and z is an alkyl having from 1 to 6 carbons.

INTERNATIONAL SEARCH REPORT

Intern .al Application No PCT/US 99/16372

A. CLASSIF	ICATION OF SUBJECT MATTER C09D11/00		
According to	International Patent Classification (IPC) or to both national class	ification and IPC	
B. FIELDS S			·
Minimum doc	cumentation searched (classification system followed by classification)	cation symbols)	
IPC 7	CO9D		•
Documentation	on searched other than minimum documentation to the extent th $\dot{}$	at such documents are included in the fields se	arched
Electronic da	ata base consulted during the international search (name of data	a base and, where practical, search terms used)
0.0001115	ENTS CONSIDERED TO BE RELEVANT		
	Citation of document, with indication, where appropriate, of the	e relevant passages	Relevant to claim No.
Category *	Oracion of document, with indication, where appropriate, or the		
X	US 5 173 112 A (MATRICK HOWARD 22 December 1992 (1992-12-22) column 2, line 40-60 column 4, line 47-68 column 6, line 50-54 column 9, line 15-20	ET AL)	1-7, 10-18
X	PATENT ABSTRACTS OF JAPAN vol. 006, no. 019 (C-090), 3 February 1982 (1982-02-03) & JP 56 143274 A (CANON INC), 7 November 1981 (1981-11-07) abstract		1-5,7, 10-14, 16-18
		-/	
X Fur	ther documents are listed in the continuation of box C.	X Patent family members are liste	d.in annex.
	ategories of cited documents:	T* later document published after the in or priority date and not in conflict with	ternational filing date
"A" docum	nent defining the general state of the art which is not idered to be of particular relevance	cited to understand the principle or t	heory underlying the
"E" earlier	document but published on or after the international	"X" document of particular relevance; the cannot be considered novel or cann	claimed invention
filing	date	involve an inventive step when the o	locument is taken alone
whic	h is cited to establish the publication date of another on or other special reason (as specified)	"Y" document of particular relevance; the cannot be considered to involve an	inventive step when the
"O" docur	ment referring to an oral disclosure, use, exhibition or	document is combined with one or r ments, such combination being obv	nore other such docu-
"P" docur	r means nent published prior to the international filing date but	in the art. "&" document member of the same pate.	
later	than the priority date claimed	Date of mailing of the international s	
	e actual completion of the international search	28/10/1999	
	20 October 1999		
Name and	d mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL – 2280 HV Rijswijk	Authorized officer	
	Tel. (+31-70) 340-2040, Tx. 31 651 epo ni, Fax: (+31-70) 340-3016	Miller, A	

INTERNATIONAL SEARCH REPORT

Inter nal Application No
PCT/US 99/16372

Category °	tion) DOCUMENTS CONSIDERED TO BE RELEVANT Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 013, no. 134 (C-581), 4 April 1989 (1989-04-04) & JP 63 297477 A (FUJI PHOTO FILM CO LTD), 5 December 1988 (1988-12-05) abstract	1,2,6,7, 10-12, 15-17
1 -		

INTERNATIONAL SEARCH REPORT

information on patent family members

Intern al Application No PCT/US 99/16372

Patent document cited in search report		Publication date	Patent family member(s)		Publication date	
US 5173112 A 2		22-12-1992	DE 4310534 A JP 2514300 B JP 6041484 A		07-10-1993 10-07-1996 15-02-1994	
JP 56143274	Α -	07-11-1981	JP JP	1006236 B 1526778 C	02-02-1989 30-10-1989	
JP 63297477	Α	05-12-1988	NONE			